



Prezzo di vendita **359,00 €**

359,00 €

radio microfono nuovo



Descrizione

Sistema UHF PLL con true diversity di 3° generazione, con funzione Remoset per il sincronismo.

36Mhz Banda 690-726Mhz

Composto da:

RU-901G3 ricevitore

RU-G3TH trasmettitore a gelato

CARATTERISTICHE RICEVITORE RU-901G3

Frequency Preparation

PLL Synthesized Control

Carrier Frequency Range UHF 470~960 MHz

Frequency Setting Remoset U Ultrasonic

Receiving Mode True Diversity

Bandwidth 36MHz

S/N Ratio > 105dB

T.H.D <0.6% @ 1KHz

Sensitivity -95dBm, S/N>80dB

CMRR >80 dB

Audio Frequency Response 50Hz~18KHz±2dB

Antenna BNC (F)

Antenna Booster Power DC12~15V/100mA

Display LCD

Display Contents Group, Channel, Frequency, Battery Status, Antenna A/B, AF Meter(LED BAR), RF Meter (LED BAR)

Controls Power ON/OFF, Group, Channel, Frequency, Audio Level, Lock-on, Volume, Output Pad, Frequency Scan (ON/OFF)

Audio Output Level Ref:±22.5KHz [Dev@1KHz Tone](#)?6.3 Phone Jack:-10dBV XLR Jack:-4dBV(Line)?-24dBV(MIC)

AF Output Impedance 600?

Squelch Pilot Tone & Noise Mute

Output Connector Balanced XLR Socket x1 / Unbalanced ?6.3mm PHONE JACK x1

Power Supply DC12~15V/500mA

Dimension (m / m) 212.3mm(W)*38.3mm(H)* 144mm(D)

Notes Actual product specifications may vary depending on region.

CARATTERISTICHE TRASMETTITORE RU-G3TH

Frequency Preparation PLL Synthesized Control

Carrier Frequency Range UHF 470~960 MHz

Frequency Setting Remoset U Ultrasonic

RF Outputs Low/High

Stability <±10KHz@ Fc

Frequency Deviation ±48KHz

Spurious Emissions <-50dBc

Display LCD+LED

Controls Power ON/OFF, Mute ON/OFF, Group, Channel, Frequency, GAIN Adjust, Auto Power Off Adjust, Lock-on Mode

Battery UM3, AA x2

Slot-in Charging Yes

Dimensions 50(W) x 253(H) x 35.5(D)

Notes Actual product specifications may vary depending on model and region.