



Prezzo di vendita 119,00 €

119,00 €

scheda audio nuovo



## Descrizione

AIR 192|4  
2-In/2-Out 24/192 USB Audio Interface

OVERVIEW FEATURES [SPECS] VIDEOS & PHOTOS SOFTWARE  
Specifications

Minimum System Requirements

- macOS: 10.8 Class Compliant
- PC: Windows 7, Windows Driver
- Standard USB 2.0 or USB-C Port

Mic Input 1 (balanced XLR)

FREQUENCY RESPONSE 20 Hz – 20 kHz (+0.1 dB)  
DYNAMIC RANGE 104 dB (A-weighted)  
SIGNAL-TO-NOISE RATIO 104 dB (+1.0 dBu, A-weighted)  
THD+N 0.003%  
PREAMP EIN -128 dBu (max gain, 150 ? source, A-weighted)  
MAX INPUT LEVEL +1.5 dBu  
GAIN RANGE 55 dB  
Line Input 1 (balanced 1/4" [6.35 mm] TRS)  
FREQUENCY RESPONSE 20 Hz – 20 kHz (+0.05 dB)  
SIGNAL-TO-NOISE RATIO 101 dB (1 kHz, +4 dBu, A-weighted)  
THD+N 0.003%  
MAX INPUT LEVEL 16 dBu  
GAIN RANGE 55 dB  
Inst Input 2 (unbalanced 1/4" [6.35 mm] TS)  
FREQUENCY RESPONSE 20 Hz – 20 kHz (+0.05 dB)  
DYNAMIC RANGE 100 dB (A-weighted)  
SIGNAL-TO-NOISE RATIO 102 dB (+ 4 dBu, A-weighted)  
THD+N 0.004%  
MAX INPUT LEVEL 6 dBu  
INPUT IMPEDANCE 1 M?  
GAIN RANGE 24 dB  
Main Outputs, L and R (balanced, differential 1/4" [6.35 mm] TRS)  
FREQUENCY RESPONSE 20 Hz – 20 kHz (+0.06 dB)  
DYNAMIC RANGE / SIGNAL-TO-NOISE RATIO 102 dB (A-weighted)  
THD+N 0.005%  
MAX OUTPUT LEVEL +7 dBu (1 kHz, -1 dBFS)  
Headphone Output (impedance-balanced 1/4" [6.35 mm] TRS)  
THD+N 0.005%  
OUTPUT IMPEDANCE 10 ?  
General  
POWER USB-bus-powered

**Nuovo: M-AUDIO AIR 192-4**

---

DIMENSIONS (WIDTH X DEPTH X HEIGHT) 8.0" x 6.0" x 2.76" (20.42 cm x 15.24 cm x 7.0 cm)  
WEIGHT 2.0 lbs. 0.9 kg