



Prezzo di vendita 149,00 €

149,00 €

scheda audio nuovo



Descrizione

Specifications

Minimum System Requirements
macOS: 10.8 Class Compliant

PC: Windows 7, Windows Driver

Standard USB 2.0 or USB-C Port

Mic Inputs 1-2 (balanced XLR)
FREQUENCY RESPONSE 20 Hz – 20 kHz (+0.1 dB)
DYNAMIC RANGE 104 dB (A-weighted)
SIGNAL-TO-NOISE RATIO 104 dB (+1.0 dBu, A-weighted)
THD+N 0.002%
PREAMP EIN -128 dBu (max gain, 150 ? source, A-weighted)
MAX INPUT LEVEL +1.5 dBu
GAIN RANGE 55 dB
Line Input 1-2 (balanced 1/4" [6.35 mm] TRS)
FREQUENCY RESPONSE 20 Hz – 20 kHz (+0.05 dB)
SIGNAL-TO-NOISE RATIO 101 dB (1 kHz, +4 dBu, A-weighted)
THD+N 0.002%
MAX INPUT LEVEL 16 dBu
GAIN RANGE 55 dB
Inst Input 1-2 (unbalanced 1/4" [6.35 mm] TS)
FREQUENCY RESPONSE 20 Hz – 20 kHz (+0.05 dB)
DYNAMIC RANGE 100 dB (A-weighted)
SIGNAL-TO-NOISE RATIO 98 dB (+ 4 dBu, A-weighted)
THD+N 0.005%
MAX INPUT LEVEL 6 dBu
INPUT IMPEDANCE 1 M?
GAIN RANGE 24 dB
Main Outputs, L and R (balanced 1/4" [6.35 mm] TRS)
FREQUENCY RESPONSE 20 Hz – 20 kHz (+0.05 dB)
DYNAMIC RANGE / SIGNAL-TO-NOISE RATIO 106 dB (A-weighted)
THD+N 0.005%
MAX OUTPUT LEVEL +13 dBu (1 kHz, -1 dBFS)
Headphone Output (1/4" [6.35 mm] TRS)
THD+N 0.005%
OUTPUT IMPEDANCE 10 ?
General
POWER USB-bus-powered
DIMENSIONS (WIDTH X DEPTH X HEIGHT) 8.0" x 6.0" x 2.76" (20.42 cm x 15.24 cm x 7.0 cm)
WEIGHT 2.1 lbs. 0.95 kg