



Prezzo di vendita 199,00 €

199,00 €

scheda audio nuovo



Descrizione

Specifications

Minimum System Requirements
macOS: 10.8 Class Compliant

PC: Windows 7, Windows Driver

Standard USB 2.0 or USB-C Port

Mic Inputs 1-2 (balanced XLR)
FREQUENCY RESPONSE 20Hz – 20kHz (+/-0.1 dB)
DYNAMIC RANGE 104dB (A-weighted)
SIGNAL-TO-NOISE RATIO 104dB (+1.0dBu, A-weighted)
THD+N 0.001% (1kHz, +0.8dBu, -1dBFS)
PREAMP EIN -126dBu (150?, unweighted)
MAX INPUT LEVEL +1.8dBu
GAIN RANGE 60dB
Line Input 1-2 (balanced 1/4" TRS)
FREQUENCY RESPONSE 20Hz – 20kHz (+/-0.1dB)
SIGNAL-TO-NOISE RATIO 101dB (1kHz, +4dBu, A-weighted)
THD+N 0.002% (1kHz, +19.7dBu, -1dBFS)
MAX INPUT LEVEL +20.7dBu
DYNAMIC RANGE 106dB (A-weighted)
Inst Input 1-2 (unbalanced 1/4" TS)
FREQUENCY RESPONSE 20Hz – 20kHz (+/-0.1dB)
DYNAMIC RANGE 106dB (A-weighted)
SIGNAL-TO-NOISE RATIO 98dB (+4dBu, A-weighted)
THD+N 0.001% (1kHz, +5.8dBu, -1dBFS)
MAX INPUT LEVEL +6.8dBu
INPUT IMPEDANCE ~1M?
GAIN RANGE 24dB
Main TRS Outputs, 1/L & 2/R (balanced 1/4" TRS)
FREQUENCY RESPONSE 20Hz – 20kHz (+/-0.1dB)
DYNAMIC RANGE 109dB (A-weighted)
THD+N 0.003% (1kHz, -1dBFS)
MAX OUTPUT LEVEL +13dBu
Main & Aux RCA Outputs 1 - 4 (Unbalanced RCA)
FREQUENCY RESPONSE 20Hz - 20kHz (+/-0.1dB)
DYNAMIC RANGE 109dB (A-weighted)
THD+N 0.003% (1kHz, -1dBFS)
MAX OUTPUT +7dBu
Headphone Outputs (Stereo 1/4" TRS)
DYNAMIC RANGE 101dB
THD+N 0.008% (1kHz, -1dBFS, 36mW)
MAX POWER 36mW (32-ohm load)

MIN IMPEDANCE 32-ohm